

PENTAX | R-2500N

Reflectorless Total Station



- Long range: reflectorless measuring up to 600 m
- Bluetooth Class1 Long Link: 100 m
- Dust & Water resistance: IP66
- Automatic Atmospheric Correction

**ADVANCED
PENTAX EDM
TECHNOLOGY**



80th
PENTAX
SURVEYING
SINCE 1933
TI Asahi Co., Ltd.
anniversary

Model	R-2501N	R-2502N	R-2503N	R-2505N
Magnification			30 x	
Effective aperture			45mm (EDM45mm)	
Resolving power			3.0"	
Field of view			2.6% (1°30')	
Minimum focus			1.0m	
Focus			Manual	
Distance measurement	Laser Class		Visible Laser: Class IIIa (Reflectorless) / Class II (Prism, sheet)	
Measurement range (Good condition) *3				
	Reflectorless *1		1.5 ~ 600m	
	Reflector sheet *2		1.5 ~ 600m (800m)	
	Mini prism		1.5 ~ 2500m (3000m)	
	1P		1.5 ~ 7000m(9000m)	
	3P		1.5 ~ 9000m(9999m)	
Accuracy *4	Prism / Reflector Sheet		1.5m ~ 10m : ±(3+2ppm x D)mm 10m ~ : ±(2+2ppm x D)mm	
	Reflectorless		1.5m ~ 150m : ±(3+2ppm x D)mm 150m ~ 300m : ±(5+2ppm x D)mm 300m ~ : ±(7+10ppm x D)mm	
At Auto-ATM. Correction	Prism / Reflector sheet		1.5m ~ 10m : ±(3+10ppm x D)mm 10m ~ : ±(2+10ppm x D)mm	
	Reflectorless		1.5m ~ 300m : ±(5+10ppm x D)mm 300m ~ : ±(7+18ppm x D)mm	
	Minimum count		0.1mm (Fine mode), 1mm (Normal mode), 10mm (Track mode)	
Measurement time *5	Repeat meas.	Normal(1mm) Quick(1mm) Track(10mm)	Prism / Ref.sheet 2.0sec. Ref.less 2.0sec. Prism / Ref.sheet 1.2sec. *6	
	Initial meas.	Normal(1mm) Quick(1mm) Track(10mm)	Prism / Ref.sheet 0.4sec. Ref.less 0.4sec. Prism / Ref.sheet 2.5sec. Ref.less 2.4sec. Prism / Ref.sheet 1.7sec. *6 Prism / Ref.sheet 2.5sec. Ref.less 2.5sec.	
Angle measurement	Measuring method		Absolute rotary encoder	
	Detection method		Vertical / Horizontal angle	
			2 sides	1 side
	Minimum count	0.5" / 1"	1" / 5"	
	Accuracy (ISO17123-3)	1"	2"	3"
Compensator	Axis	3 axis *7		2 axis
	Range	±3'		
Tangent Screw		1 Speed		
Sensitivity of vials	Plate level	20"/1div. (electronic)	30"/1div. (electronic)	30"/1div.
	Circular level	8/2mm		
Plummet		Visible Laser, ±0.5mm (instrument height 1.5m)		
Base	Dust and Water Protection	Detachable IP66 (instrument only)		
Ambient temperature		-20°C ~ 50°C / -4°F ~ 122°F (Working range)		
Tripod thread		5/8"x 11		
Dimensions/Weight	Dimensions	190(W) x 343(H) x 177(L)mm		
	Weight (incl. Battery)	5.7kg		
	Carrying case	373(W) x 286(H) x 465(L)mm / 2.9kg		
Battery pack BP07	Power source	Li-ion 2500mAh x 2 (hot swap)		
	Operation time	Continuous approx. 4.5 hrs (ETH+EDM), 15 hrs (ETH) with approx. 2.2 hrs of charging time		
	Weight	110g x 2 pcs		
Battery charger BC05 and AC Adapter AC05	Input voltage (AC05)	AC 100 ~ 240V		
	Output voltage (BC05)	DC8.4V		
Data Process	Data recording method	Internal Memory		
	Coordinates data *8	60,000		50,000
	Special function	PowerTopoLite		
	I/F	RS-232C, SD CARD, USB, Bluetooth		
Display / Keyboard	Display type	Graphic LCD / 20 characters x 8 lines / 240 x 96 pixels		
Quantity		2		
Keys		22 each(12 numeric / 5 function / 5 special)		
Display back light		Intensity settings: 10 steps		
Laser Pointer		Yes		
Date clock		Yes		

* Specifications are subject to change without notice

- *1 The measurement range and accuracy of reflectorless, and time required to measure may vary by the shape, size of surface area and reflection rate of the target and its environment.
The measurement range of reflectorless is determined by the white side of the Kodak Gray Card.
- *2 Reflector sheet: PENTAX genuine Reflector sheet
- *3 The measurement range may vary by conditions of the environment.
Normal conditions: 20km visibility with slight shimmer
Good conditions: 40km visibility, overcast, no heat, no shimmer and moderate wind.
- *4 When automatic atmospheric correction is on, the EDM error is 10ppm in prism and reflector sheet mode.
- *5 EDM measuring time is determined in good conditions. It may takes longer than usual to measure the distance exceeding 4000m in prism mode and 300m in reflectorless mode.

- *6 Quick mode, which functions with prism and reflector sheet, is effective only under normal mode(1mm) and up to 500m.
- *7 In addition to dual-axis correction in the (X) and (Y) direction, mechanical error in the instrument is corrected.
- *8 Number of points to be recorded may vary by usage.
Maximum number of point to be recorded per job site : 3000 points
Maximum number of job file to be recorded : 50 job files
Maximum data points to be sent from PC to the instrument: 3000 points

TI Asahi Co., Ltd.
International Sales Department
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi
 Saitama, 339-0073 Japan
 Tel.: +81-48-793-0118
 Fax: +81-48-793-0128
 E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.

JSIMA
 Japan Surveying Instruments Manufacturers' Association
 Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.