CIRCULAR & PLATE LEVEL CUSTOMISATION





AL 10 Tribach Adapter SP ADSTAALPL

Various types of **Replacement Bubbles**

surveying equipment.

To expand our product range to suit all users, Horizon offers a wide range of replacement Bubbles to customise your



SP HZOLS024CL

II H III II

HTS 300 / ET 1000 Series

SP ETHTSPIO1





LC SPOL641990





	Model	Order Number	Sensitivity of Bubble
Circular Level	HZ 2000 Series	SP OLT2000CL	8'/2mm
	HZ 4024	SP HZOLS024CL	8′/2mm
	HZ 4032	SP HZOLS032CL	8′/2mm
	AJ10 / AJ13	SP ADSTBAJCL	8′/2mm
	NA 700 Series	LC SPOL641990	10′/2mm
	NA 800 Series	LC SP434239	10′/2mm
Plate Level	AL 10 Tribrach Adapter	SP ADSTAALPL	30'/2mm
	HTS 300 / ET 1000 Series	SP ETHTSPLO1	30'/2mm

HIGH QUALITY & WIDE RANGE OF COMPASSES

With a wide range of quality Compasses, Horizon has something to offer to every industry that needs one. From a simple Pocket Compass to Optical Compasses to even those for Forestry Survey.

Our range of Compasses

will serve a wide range of



DC45-3 Compass DQY-M Mecca Seeking Pocket Compass HZ MCDC45-3 HZ PCIQYM





DQL-3 Pocket Compass HZ PCHQL3

DQL-2A Pocket Compass DQL-1 Forestry Compass HZ OCHDQL1 HZ PCHQL2A



HZ PCHDQY1

applications.



HZ PCHQL8





H7 MCDC45-1

DC45-2 Compass H7 MCDC45-2

DSL-1 Forestry Compass HZ ODLHDSL1

DQL-6 Optical Compass HZ OCHQL6



MEASURING WHEELS

Classique Professional

- Measures up to 10km by 10cm units
- Metric or Imperial
- Pistol Grip Zero Reset
- Trigger Brake •
- Kick Down Side Stand .
- Sealed Roller Bearings •
- Wrist Strap
- In Line Weight Distribution for Balance
- Folds in Half
- **Optional Carry Case** .
- Full One Year Guarantee

Measuring wheel 500 deluxe

500mm Circumference wheel for accuracy as well as for convenience and compact storage. Folds easily to one third of it's length and snaps back to full length.

- Wheel Circumference :500mm
- Wheel Diameter : 160mm
- Maximum Distance :999.9m
- Reading : Meters, Decimeters
- Weight 1.1kg

MW 500 Bantam

Net Weight : 0.77 kg

Other specifications same as MW Mini 500











